for more products please visit us on mw-antenna.com

Horn Antenna 5GHz 18dBi Dual Polarization For

Horn Antenna 5GHz 18dBi Dual Polarization For WISP

Basic Information

Place of Origin: China
Brand Name: Famous
Certification: CE ISO9001
Model Number: Horn Antenna
Minimum Order Quantity: 1 SET
Price: Negotiable

Packaging Details: Standard export packaging/customizable

packaging

• Payment Terms: T/T L/C



Product Specification

Name: Symmetrical Horn Antenna

• Diameter Of Mounting Pole: Φ51~Φ114 Mm

• Antenna Connection: Waveguide (special Made By Dongguan

Famous Precision) Or SMA

• Net Weight: 2.5kgs/5.5lb

Material: UV Stabilized PC, Aluminum Alloy

Wind Survivability: 200 Km/hWind Loading: 200 Km/h

• Mechanical Adjustment: ±25° Elevation, ±25° Azimuth

Pole Compatibility: Ø40 To 60 Mm

• Weatherproofing: IP55

• Highlight: Horn Antenna 5GHz 18dBi,

Dual Polarization Horn Antenna, WISP microwave horn antenna



Product Description

Horn Antenna 5GHz 18dBi Dual Polarization For WISP

- Aluminum Die Casting Horn and Bracket
- Noise rejection and isolation band reuseEasy to amount, easy to adjust antenna elevation angle
- Small size, light weight, less wind load, need less space on Tower
 Include two pigtail cable assembly, N male to RPSMA

Electrical performance:

	Frequency Range (GHz)	Gain (dBi)	Azimuth Beam Width -3dB	Elevation Beam Width -3dB	Azimuth Beam Width -6dB	Elevation Beam Width -6dB	Front/Back Ratio(dB)	1 -	Polariz ation	
3 0°	5.0-7.0	18	H21° V21°	H21° V21°	H30° V30°	H30°	37	≤1.8	Dual- Linear	
4 0°	5.0-7.0	16	H27° V27°	H27° V27	H40° V40°	H40° V40°	35	≤1.8	Dual- Linear	
5 0°	5.0-7.0	14	H33° V33°	H33° V33°	H50° V50°	H50° V50°	33	≤1.8	Dual- Linear	
6 0°	5.0-7.0	13	H41° V41°	H41° V41°	H60° V60°	H60° V60°	32	≤1.8	Linear	
7 0°	5.0-7.0	11	H50° V50°	H50° V50°	H70° V70°	H70° V70°	30	≤1.8	Dual- Linear	
8 0°	5.0-7.0	10	H60°	H60° V60°	H80° V80°	H80° V80°	29	≤1.8	Linear	
9 0°	5.0-7.0	9	H67° V67°	H67° V67°	N90°	N90°	28	≤1.8	Dual- Linear	
Ar	itenna Connectio	on	Waveguide (s	Waveguide (special made by Dongguan Famous Precision) or SMA						
Ne	et Weight		2.5kgs/5.5lb	2.5kgs/5.5lb						
М	aterial		UV stabilized	UV stabilized PC, aluminum alloy						
W	ind survivability		200 km/h	200 km/h						
W	ind loading		200 km/h	200 km/h						
М	ounting			Mechanical adjustment: ±25° elevation, ±25° azimuth Pole compatibility: Ø40 to 60 mm						
W	eatherproofing		IP55	IP55						





Wuxi Famous Communication Equipment Co., Ltd.

+86 13255118228

eric@mw-antenna.com



mw-antenna.com

Room 803, Wisdom Building, No. 18 Wisdom Road, Huishan Economic Development Zone, Huishan District, Wuxi City, Jiangsu Province, China